

underwater vision specialists

Features

- High Resolution Colour 650 TVL
- 10 Bit Digital Processing
- Low Light Sensitivity 0.1 Lux
- 65° Diagonal Angle of View
- 4,000 or 6,000 Metre Rated Titanium Housing



Description

The Bowtech Products L3C-650 miniature high resolution underwater colour CCD camera, provides a low cost solution to general underwater viewing and observation.

The camera housing is manufactured with high quality titanium, rated to 4,000 metres operating depth, with a 6,000 metre option.

The camera is fitted with a fixed focus wide angle lens, giving a diagonal field view of 65° in water, through a sapphire window. The camera features built-in reverse polarity and surge protection.

The miniature, high quality Sony 1/3" EX-View HAD CCD sensor, offers high resolution and low light level sensitivity, achieved by using 10 bit digital processing. It is the ideal camera for underwater viewing tasks.





Specification - L3C-650

ELECTRICAL

Resolution, Horizontal: 650 TV Lines Limiting Light Sensitivity: 0.1 Lux @ f2.0

Sensor Type: 1/3" (Sony) EX-view HAD CCD, 10 Bit Digital Processing

Sensor Elements: 752 (H) x 582 (V) PAL, 768 (H) x 494 (V) NTSC

Signal to Noise Ratio: >52dB

Scanning: 625 Line 50Hz PAL, 525 Line 60Hz NTSC

Voltage: 12 to 24Vdc
Current: 130mA Maximum
Composite Video Output: 1.0V pk-pk

Electro-magnetic Compatibility: EN50081-1 Emission/EN500852-1 Immunity

MTBF: 80,000 hrs

ENVIRONMENTAL

Water Depth: 4,000 or 6,000m Option

Storage Temperature: -30 to +70°C

Operating Temperature: -10 to +50°C (maximum 2 hrs in-air operation)
Shock: 3 Axis (operating), 30g Peak, 6ms Half-sine Pulse

OPTICAL

Lens: f2.0, 2.9mm or 3.6mm,4.3,6,8,12,16
Auto Iris: CCD Iris 1/50th to 1/100,000th sec.

Focus: Fixed 100mm to Infinity

Angle of View: 91° Diagonal in Air, 65° in Water (2.9mm lens)

Window: Sapphire Glass

MECHANICAL


Maximum Diameter: 31mm

Length: 133.2mm Excluding Connector Weight in Air: 266g (when fitted with MCBH4M)

Weight in Water: 157g Standard Housing: Titanium

Standard Connector: WETCON BH-4-MP or MCBH4M

Optional Connectors: Large Selection of Connectors Available



BH Wetcon 55 Series 15 Shell MSAJ/MSSJ

LPMBH

LPBH

MCBH Micro Wetcon RA MCBH Micro Wetcon

(connector face patterns not to scale)





T +44 1224 772345 F +44 1224 772900

sales@bowtech.co.uk www.bowtech.co.uk